

UNMANAGED POWER DISTRIBUTION UNITS (PDUs)

IEC, VERTICAL AND HORIZONTAL, 10A | 16A



PowerShield Unmanaged full metal rackmount PDU's are highly reliable, multiple outlet power strips designed to deliver conditioned power to mission-critical networking, server or telecom equipment often used in conjunction with an uninterruptible power supply (UPS).

FEATURES

- Built in 6kA C-Curve MCB Circuit Breakers with on/off switch
- Includes 10 or 16 Amp, 3-Pin Australian/New Zealand plug, ideal for connecting to UPSs
- Vertical PDUs incorporate three-way mounting brackets for ease of installation
- Horizontal PDUs incorporate recessed brackets for cable management



HORIZONTAL RANGE

RPR-IEC-10A10H
10 Outlet Horizontal Power Rail



RPR-IEC-16A10H
10 Outlet Horizontal Power Rail



RPR-IEC-16A20H
20 Outlet Horizontal Power Rail



VERTICAL RANGE

**Vertical 3 Sided
Mounting Bracket**



RPR-IEC-10A10V
10 Outlet Vertical Power Rail



RPR-IEC-16A10V
10 Outlet Vertical Power Rail



RPR-IEC-16A20V
20 Outlet Vertical Power Rail



UNMANAGED POWER DISTRIBUTION UNITS

Model Number	RPR-IEC-10A10H	RPR-IEC-16A10H	RPR-IEC-16A20H	RPR-IEC-10A10V	RPR-IEC-16A10V	RPR-IEC-16A20V
INPUT						
Voltage	230VAC (Nominal)					
Voltage Range	200–240VAC					
Frequency Range	50Hz or 60Hz ± 1Hz					
Cable (2m)	C14	C20	C20	C14	C20	C20
OUTPUT						
10A Outlets (IEC C13)	10	8	16	10	8	16
16A Outlets (IEC C19)	0	2	4	0	2	4
OPERATING ENVIRONMENT						
Temperature	–10°C – +40°C					
Storage Temperature	–10°C – +60°C					
Humidity	5% (0°C)–90% (40°C)					
DIMENSIONS						
Dimensions W x D x H (mm)	482 x 95 x 45	482 x 95 x 45	482 x 95 x 90	752.5 x 67 x 50	752.5 x 67 x 50	1327.5 x 67 x 50

PLUG POWER, VERTICAL AND HORIZONTAL, 10A | 16A OPTION



AUSTRALIAN DESIGNED
POWER PROTECTION
SOLUTIONS



HORIZONTAL RANGE

RPR-6HMCB

10A plug, 6 x 10A Outlet,
1RU Horizontal Power Rail



RPR-10HMCB

10A Plug, 10 x 10A Outlet,
2RU Horizontal Power Rail



VERTICAL RANGE

Vertical 3 Sided
Mounting Bracket



RPR-20VMCB

10A Plug, 20 x 10A Outlet, Vertical Power Rail



RPR-10VMCB

10A plug, 10 x 10A Outlet, Vertical Power Rail



RPR-10V15MCB

15A plug, 10 x 10A Outlet, Vertical Power Rail



RPR-15VMCB

10A plug, 15 x 10A Outlet, Vertical Power Rail



RPR-20V15MCB

15A plug, 20 x 10A Outlet, Vertical Power Rail



UNMANAGED POWER DISTRIBUTION UNITS

Model Number	RPR-6HMCB	RPR-10HMCB	RPR-10VMCB	RPR-15VMCB	RPR-20VMCB	RPR-10V15MCB	RPR-20V15MCB
INPUT							
Voltage	240VAC (Nominal)						
Voltage Range	50Hz or 60Hz ± 1Hz						
Plug	Australian/New Zealand 10A, 3-Pin					Australian/New Zealand 15A, 3-Pin	
Cable Length (m)	2	2	.75	1	1.3	2	2
Ow							
Outlets	6	10	10	15	20	10	20
OPERATING ENVIRONMENT							
Temperature	−10°C – +40°C						
Humidity	5% (0°C)–90% (40°C)						
DIMENSIONS							
Dimensions W x D x H (mm)	482.50 x 95 x 45	482.60 x 95 x 90	752.50 x 67 x 50	1040 x 67 x 50	1327.50 x 67 x 50	752.50 x 67 x 50	1327.50 x 67 x 50